



## OUTDOOR VMD

✉ sales@sensesecure.in | service@sensesecure.in | support@sensesecure.in

🌐 www.sensesecure.in 📞 1800-889-4139

## OUTDOOR LED BOARD

Visual Display Unit/ Variable Message Display



- True/RGB Color Full-Matrix Outdoor VMS.
- True/RGB Color Full-Matrix Indoor VMS.
- Complies with EN12966 standard.
- 4/5/6/8/10 mm pixel pitch options.
- Hi-Bright Wide-Angle LED pixel(RGB) for day light visibility.
- Direct current constant drive technology.
- Pixel-wise failure detection and Health-status reporting.
- High life expectancy, Low Maintenance.
- Configurable Line attributes such as Steady, Flash, Partial-Flash, Right-Left-Top-Bottom-Center Entry, Blank etc.
- Multiple languages and Multiple Font Size options, as supported by WINDOWS
- Message storage and Scheduler facility.
- 10 stage dimming facility with software and photo-sensors.
- Supports multiple formats like WORD, XLS, BMP, JPEG, Video, RSS.
- LED Modules with IP65 ingress protection and enclosure with sense facility for Door Open, Temperature and Humidity.
- Message transfer to remote location via wired(Ethernet-TCP/IP) or wireless(2G/3G/4G) data channel.
- User friendly software for Control Room Operation.